



Therm-O-Flow[®]

Bulk Warm Melt Systems



PROVEN QUALITY. LEADING TECHNOLOGY.

Therm-O-Flow Bulk Warm Melt Systems

Precision Temperature Control

Designed specifically for warm melt materials and temperature conditioning applications, Graco Therm-O-Flow Warm Melt Supply Systems deliver superior heat control and performance in a reliable, easy-to-use, easy-to-maintain package. Instead of investing in a custom solution or equipment meant for other applications, Graco Therm-O-Flow Warm Melt Supply Systems offer performance and flexibility at a reasonable price.

Low/Empty Level Sensors

Standard on every system. Adjustable, so you never run out of material unexpectedly.

Precision Temperature Control

Ensures consistent processes with accurate temperature control of up to 32 defined heat zones

Large Ram Cylinders

Increases pump loading and flow rate capability for high viscosity materials

Check-Mate® Pump

For trouble-free long life and reliable material movement

Integrated Drum Air Blow-Off

Reduces downtime with quick, easy drum changes

Optional Light Tower Accessory

Lets operator know the unloader status from a distance, indicating readiness, alarms and warnings

Advanced Display Module

Easy-to-use, graphic-based control screens reduce training time. Data downloads allow for better process monitoring and control.

Easy Access Air Controls

Lets you control motor, ram and blow-off air independently

Pump + Platen Options

- Choose between ambient and heated pump and platen for greater application flexibility
- Minimizes leftover material and reduces waste
- Long-lasting, one-piece platen seals are easy to replace



THERM-O-FLOW WARM MELT 200 L (55 GAL)

Improve Your Productivity and Throughput

Applications:

- Window glazing
- Insulating glass
- Window manufacturing
- Automotive interiors
- Automotive structural and BIW applications
- Cable manufacturing
- Furniture assembly
- Door lamination
- Tape and label manufacturing
- Solar panels
- Advanced composites
- And more...

Materials:

- Warm melt sealers
- Urethanes
- Epoxies
- Prepreg resin mixes
- Structural Adhesives
- Silicones
- Paraffin Wax
- And others...



THERM-O-FLOW WARM MELT 20 L (5 GAL)

Why Therm-O-Flow?

Improve process efficiency

- Automatic electric crossover eliminates downtime with tandem units – you keep production running while you change drums or pails
- Sensors signal when drums are getting low or empty, and more material is needed
- Pump throat seals and plate seals are the only wear components on Therm-O-Flow and can be changed in less than one hour
- Proven Check-Mate lowers available in Standard Severe Duty or MaxLife® for longer life over standard offering

Improve Application Options

- Therm-O-Flow Warm Melt offers greater application flexibility while configuring complex applications
- Eliminates need for add on heat controls — melts resins on demand, only what you need
- Automatic daily startup without delay — Therm-O-Flow Warm Melt is ready when the shift starts
- Use downloadable operating data to monitor and control your process, reducing unplanned downtime and increasing process efficiency

Reduce energy costs

- Temperature setback conserves energy during production breaks and prevents material charring
- Inactivity shutoff saves energy costs, promotes safety and prevents material charring

Support environmental initiatives

- Built-in runaway control automatically shuts down supply system in event of component failure or empty drum
- The quiet, low-noise NXT Air Motor operates around 90 decibels, while other comparable motors operate up to 103 decibels

A Complete Line of Therm-O-Flow Systems

No matter what the application,
Graco has a bulk warm melt solution



Therm-O-Flow Warm Melt 200 L

- The ultimate warm melt supply system
- Highest throughput in the industry
- Provides accurate temperature control for heat zones up to 32 zones
- Main unit easily integrates with a second Therm-O-Flow Warm Melt unit for tandem operation (up to 32 customer defined heat zones with expansion boxes)
- Combine multiple Therm-O-Flow Warm Melts units in parallel for even higher flow rates



Therm-O-Flow Warm Melt 20 L and 60 L

- Perfect for 5 gallon (20 liter) and 16 gallon (60 liter) applications in both low and high flow settings
- Provides accurate temperature control of heat zones up to 32 zones
- Main unit easily integrates with a second Therm-O-Flow Warm Melt unit for tandem operation (up to 32 customer defined heat zones)
- Compact footprint lets you place unit near application [45" x 20" (114.3 x 50.8 cm) approx.]

Better performance. More heat zones. More configurations.

Model	Pump Style	Container Size	Max Zones	Cycle Rate	Viscosity
Therm-O-Flow Warm Melt 20	Check-Mate Priming Piston Pump	5 gallons (20 liters)	32	60 CPM	Low to high
Therm-O-Flow Warm Melt 60	Check-Mate Priming Piston Pump	16 gallons (60 liters)	32	60 CPM	Low to high
Therm-O-Flow Warm Melt 200	Check-Mate Priming Piston Pump	55 gallons (200 liters)	32	60 CPM	Low to high

Components of the Therm-O-Flow Supply System



Major Components	Nozzle or Tip	Dispense Valves	Dispense Hoses	Fluid Regulators*	Metering System	Pipe Manifold**	Supply Hoses	Supply Pumps
Selection Factors	<ul style="list-style-type: none"> • Size, shape, and type of fluid flow pattern 	<ul style="list-style-type: none"> • Usage <ul style="list-style-type: none"> - Manual - Pneumatic - Robotic - Shot • Pressure • Volume 	<ul style="list-style-type: none"> • Viscosity • Volume • Length • Pressure • Flexibility • Chemical compatibility 	<ul style="list-style-type: none"> • Viscosity • Pressure • Volume • Chemical compatibility 	<ul style="list-style-type: none"> • Viscosity • Pressure • Flow rate • Dispense points • Level of fillers 	<ul style="list-style-type: none"> • Viscosity • Pressure • Location • Drops • Chemical compatibility 	<ul style="list-style-type: none"> • Viscosity • Volume • Length • Pressure • Chemical compatibility 	<ul style="list-style-type: none"> • Container size • Volume • Viscosity • Pump location • Chemical compatibility
Equipment Options	<ul style="list-style-type: none"> • Nozzles • Tips • Extensions • Brushes 	<ul style="list-style-type: none"> • Mechanical gun • Pneumatic gun <ul style="list-style-type: none"> - Nozzle - Extrusion - Spray - Length - Orifice 	<ul style="list-style-type: none"> • Steel, SST • Pipe JIC • Flexible hoses <ul style="list-style-type: none"> - PTFE - Buna - Nylon - Moisture-Lok 	<ul style="list-style-type: none"> • Mastic regulator • Pressure compensating valve 	<ul style="list-style-type: none"> • Volume control • Continuous flow 	<ul style="list-style-type: none"> • Steel • SST • Pipe • Tubing • Sizes 	<ul style="list-style-type: none"> • Steel, SST • Pipe JIC • Flexible hoses <ul style="list-style-type: none"> - PTFE - Buna - Nylon - Moisture-Lok 	<ul style="list-style-type: none"> • Priming piston • Double ball • Ram mount • Single or dual wipers • Drum empty options • Auto crossover

*Not shown - fluid regulators are required for manual applications. For automated dispensing systems, metering systems are required.

**Not shown - pipe manifold is dependent on material and application.

Technical Specifications

Therm-O-Flow Warm Melt

Maximum Fluid Operating Temperature	158°F (70°C)
Maximum Air Motor Cycle Rate	60 cycles per minute
Air Inlet Size (Supply System)	3/4" npt (f)
Air Motor Sound	90 dBA at 100 psi
Ambient Operating Temperature Range (Supply System)	32–120°F (0–49°C)

Maximum Working Pressure

36:1	3600 psi (28 MPa, 276 bar)
68:1	6800 psi (34 MPa, 375 bar)

Platen Wetted Materials

5 gallon (20 liter)	Electroless nickel plated ductile iron, EPDM, PTFE coated aluminum, 6061 aluminum, Buna, Viton, Zinc plated steel, 316 stainless steel, 17-4 stainless steel
16 gallon (60 liter)	Electroless nickel plated ductile iron, EPDM, PTFE coated aluminum, 6061 aluminum, Buna, Viton, Zinc plated steel, 316 stainless steel, 17-4 stainless steel
55 gallon (200 liter)	319 cast aluminum, EPDM, Zinc plated carbon steel, 17-4 stainless steel

Electrical Requirements

Heated 5 gallon (20 liter), 16 gallon (60 liter)	200-240 VAC, 1 phase, 50/60 Hz, 19 A 200-240 VAC, 3 phase, 50/60 Hz, 8 A 380-420 VAC, 3 phase (YN), 50/60 Hz, 8 A 480 VAC, 3 phase, 50/60 Hz, 4 A
Ambient 5 gallon (20 liter), 16 gallon (60 liter)	200-240 VAC, 1 phase, 50/60 Hz, 16 A 200-240 VAC, 3 phase, 50/60 Hz, 8 A 380-420 VAC, 3 phase (YN), 50/60 Hz, 8 A 480 VAC, 3 phase, 50/60 Hz, 4 A
Heated 55 gallon (200 liter)	200-240 VAC, 1 phase, 50/60 Hz, 28 A 200-240 VAC, 3 phase, 50/60 Hz, 16 A 380-420 VAC, 3 phase (YN), 50/60 Hz, 16 A 480 VAC, 3 phase, 50/60 Hz, 8 A
Ambient 55 gallon (200 liter)	200-240 VAC, 1 phase, 50/60 Hz, 16 A 200-240 VAC, 3 phase, 50/60 Hz, 8 A 380-420 VAC, 3 phase (YN), 50/60 Hz, 8 A 480 VAC, 3 phase, 50/60 Hz, 4 A

Fluid Outlet Size

Check-Mate 200	1" npt (f)
----------------	------------


Maximum Air Input Pressure Supply System

5 gallon (20 liter)	150 psi (1.0 MPa, 10 bar)
16 gallon (60 liter)	150 psi (1.0 MPa, 10 bar)
55 gallon (200 liter)	120 psi (0.9 MPa, 9 bar)

Ordering Information

Selection of the Therm-O-Flow Warm Melt System

The Therm-O-Flow Warm Melt System provides the flexibility to configure a system to meet your specific needs. This includes different combinations of pump, ram sizes, platen, interface and power options.



WM = Therm-O-Flow Warm Melt System

Check-Mate Pump Options

	Size	Pump Material	Heated/Ambient
C1	36:1	CS	Ambient*
C2	36:1	CS	Heated ≤ 158F°
C3	36:1	CM	Ambient*
C4	36:1	CM	Heated ≤ 158F°
C5	68:1	CS	Ambient*
C6	68:1	CS	Heated ≤ 158F°
C7	68:1	CM	Ambient*
C8	68:1	CM	Heated ≤ 158F°

Rams Options

	Name	Ram Size	Drum Size
1	D60	3 in.	5 gal (20 L)
2	D200	3 in.	55 gal (200 L)
3	D200s	6.5 in	55 gal (200 L)

Platen and Seal Options

	Platen Size	Platen Material	Seal Material	Wiper	Heated/Ambient
A	5 gal (20 L)	CST/AL	EPDM	Single Ring	Ambient
B	5 gal (20 L)	CST/AL	EPDM	Single Ring	Heated ≤ 158F°
C	16 gal (60 L)	CST/AL	PTFE Coated Nitrile	Single Flat	Ambient
D	16 gal (60 L)	CST/AL	PTFE Coated Nitrile	Single Flat	Heated ≤ 158F°
F	55 gal (200 L)	AL	EPDM	Double Ring	Ambient
G	55 gal (200 L)	AL	EPDM	Double Ring	Heated ≤ 158F°

Interface/Power Options

A system without an ADM option is only used as part of tandem system

	Platen Size	Power
1	ADM	240V
2	ADM	480V
3	No ADM	240V
4	No ADM	480V

KEY:

CS = Carbon Steel Severe Duty

CM = Carbon Steel MaxLife®

CST/AL = Carbon Steel/Aluminium

AL = Aluminium

* When the system is configured with an ambient pump, only an ambient platen is available. An ambient pump allows for additional accessory heat zones.



ABOUT GRACO

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Distribution Center
Graco Distribution BV
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Fluid Equipment
(Shanghai) Co.,Ltd
Building 7, No. 1-2,
Wenshui Road 299
Jing'an District
Shanghai 200436
P.R. China
Tel: 86 512 6260 5711
Fax: 86 21 6495 0077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 432, Augusta Point
Regus Business Centre 53
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4208
Fax: 91 124 435 4001

JAPAN


Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
38, Samsung 1-ro 1-gil
Hwaseong-si, Gyeonggi-do, 18449
Republic of Korea
Tel: 82 31 8015 0961
Fax: 82 31 613 9801

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is certified ISO 9001.



Europe
+32 89 770 700
FAX +32 89 770 777
WWW.GRACO.COM