



FAST-BALL® 100 PUMP

Designed for Enhanced Quality, Durability and Reliability

When you purchase Graco, you expect the best. The fully redesigned Fast-Ball delivers unmatched Graco performance and operation. Its simple, easy-to-install design allows for efficient serviceability to minimize downtime and keep your operations running.

In-Line Design

- Means fewer parts for less pump wear

Double-Acting Pump

- Provides reliable fluid flow

Differential Air Motor

- Ensures smooth pump operation

5-Year Warranty

- Graco's quality guarantee and peace of mind

SPECIFICATIONS

Air Inlet Size	1/4 in NPT
Air Operating Range	40-150 psi (2.8-10.3 bar)
Compatible Material	Oil, Gear Lube, ATF
Maximum Fluid Flow	12.5 gpm (47.3 lpm)
Fluid Inlet Size	1 in NPT
Fluid Outlet Size	3/4 in NPT
Maximum Air Inlet Pressure	150 psi (10.3 bar)
Maximum Continuous Cycle Rate	100 cpm
Maximum Working Pressure	150 psi (10.3 bar)
Power Type	Pneumatic
Pump Ratio	1:1
Sound Power Level	78 dB(A)
Weight	2.9-4.4 kg (6.3-9.8 lbs)

FAST-BALL 100 PUMPS

PART NUMBER	DESCRIPTION
279035	Universal Length Pump
279036	Cut-to-Length PVC Downtube Pump
279037	200 Liter (55 Gallon) Drum Length Pump



TYPICAL APPLICATIONS

- ▶ Fluid Transfer
- ▶ Specialty Fluid Dispenses
- ▶ Point of Use
- ▶ Mobile Fluid Carts

For more information, visit graco.com/vehicle-service.